



Working Voltage: 33 V
Peak Pulse Power: 600 W

Features

- Glass passivated chip
- 600 W peak pulse capability with a 10/1000 μ s waveform, repetitive rate (duty cycle): 0.01 %
- High reliability application and automotive grade
- AEC-Q101 qualified
- Low leakage
- Bidirectional unit
- Excellent clamping capability
- Very fast response time
- RoHS compliant

Mechanical Data

- Case: Molded plastic
- Epoxy: UL 94V-0 rate flame retardant
- Lead: Solderable per MIL-STD-750, method 2026
- Polarity: Color band denotes cathode end except Bipolar
- Mounting position: Any

SMB/ DO-214AA


Dimensions: inch [mm]

Maximum Ratings($T_A=25^\circ\text{C}$ unless otherwise noted)







Parameter	Symbol	Value	Unit
Peak power dissipation with a 10/1000 μ s waveform ⁽¹⁾	P _{PP}	600	W
Peak pulse current with a 10/1000 μ s waveform ⁽¹⁾	I _{PP}	See Next Table	A
Power dissipation on infinite heatsink at $T_L = 75^\circ\text{C}$	P _D	5.0	W
Peak forward surge current, 8.3 ms single half sine-wave unidirectional only ⁽²⁾	I _{FSM}	100	A
Maximum instantaneous forward voltage at 50 A for unidirectional only ⁽³⁾	V _F	3.5/5.0	V
Operating junction and storage temperature range	T _J , T _{STG}	-55 to +150	°C

Note:

(1)Non-repetitive current pulse per Fig.5 and derated above $T_A = 25^\circ\text{C}$ per Fig.1

(2)Measured on 8.3 ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum

(3)V_F<3.5V for devices of V_{BR}<200V and V_F<5.0V for devices of V_{BR}>201V

Ratings and Characteristics Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)

Fig. 1 - Pulse Derating Curve

Fig. 2 - Maximum Non-Repetitive Surge Current

Fig. 3 - Steady State Power Derating Curve

Fig. 4 - Peak Pulse Power Rating Curve

Fig. 5 - Pulse Waveform

Fig. 6 - Typical Junction Capacitance

Electrical Characteristics($T_A=25^\circ\text{C}$ unless otherwise noted)

Part Number (Bi)	Device Marking Code	Breakdown Voltage $V_{BR} @ I_T$			Maximum Reverse Leakage I_R @ V_{RWM} (uA)	Working Peak Reverse Voltage V_{RWM} (V)	Maximum Reverse Surge Current I_{PP} (A)	Maximum Clamping Voltage V_C @ I_{PP} (V)
	Bi	Min (V)	Max (V)	I_T (mA)				
SMBJ33CAHE3_A/H-CN	CMA	36.70	40.60	1	1	33.0	11.26	53.3

Note:

1. Add suffix ' CA ' after part number to specify Bi-directional devices
2. For Bi-Directional devices having V_R of 10 volts and under, the I_R limit is double

NOTICE

The information presented in this document is for reference only. Involving product optimization and productivity improvement, ChipNobo reserves the right to adjust product indicators and upgrade some technical parameters. ChipNobo is entitled to be exempted from liability for any delay or non-delivery of the information disclosure process that occurs.

本文件中提供的信息仅供参考。涉及产品优化和生产效率改善, ChipNobo 有权调整产品指标和部分技术参数的升级, 所出现信息披露过程存在延后或者不能送达的情形, ChipNobo 有获免责权。

The product listed herein is designed to be used with residential and commercial equipment, and do not support sensitive items and specialized equipment in areas where sanctions do exist. ChipNobo Co., Ltd or anyone on its behalf, assumes no responsibility or liability for any damages resulting from improper use.

此处列出的产品旨在民用和商业设备上使用, 不支持确有制裁地区的敏感项目和特殊设备, ChipNobo 有限公司或其代表, 对因不当使用而造成的任何损害不承担责任。

For additional information, please visit our website <http://www.chipnobo.com>, or consult your nearest Chipnobo sales office for further assistance.

欲了解更多信息, 请访问我们的网站 <http://www.chipnobo.com>, 或咨询离您最近的 Chipnobo 销售办事处以获得进一步帮助。