


Zener Voltage 3.3 ~ 200 V

5.0 Watt Power Dissipation

DO-27



Unit: inch(mm)

Features

- Glass passivated chip
- Built-in strain relief
- Low inductance
- High peak reverse power dissipation
- Low reverse leakage
- For use in stabilizing and clipping with high power rating
- RoHS compliant

Mechanical Data

- Case: DO-27 Molded plastic
- Lead: Solderable per MIL-STD-750, method 2026
- Epoxy: UL 94V-0 rate flame retardant
- Polarity: Color band denotes cathode end
- Mounting position: Any

Parameter	Symbols	Value	Unit
DC Power dissipation at $T_L = 75^\circ\text{C}^{(1)}$	P_D	5.0	W
Maximum forward voltage at $I_F=200\text{mA}$	V_F	1.2	V
Junction temperature range	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$
Storage temperature range	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$

Note :

(1) T_L =Lead temperature at 3/8" (9.5mm)from body

Ratings and Characteristics Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)




Fig. 1 - Power Temperature Derating Curve




Fig. 2 - Temperature Coefficients v.s. Zener Voltage




Fig. 3 - Typical Thermal Resistance v.s. Lead Length




Fig. 4 - Maximum Surge Power




Fig. 5 - Typical Thermal Response L, Lead Length=3/8inch

Part Number	Nominal Zener Voltage @I _T			I _{ZT} (mA)	Maximum Zener Impedance			Maximum Reverse Leakage Current		Maximum DC Zener Current
	V _{Z AVE.} (V)	V _{Z MIN.} (V)	V _{Z MAX.} (V)		Z _{VT} MAX.(Ω) @I _{ZT}	Z _{ZK} MAX.(Ω) @I _{ZK}	I _{ZK} (mA)	I _R (uA) @V _R	V _R (V)	
1N5333	3.3	3.14	3.47	380	3.0	400	1.00	300	1.0	1437.0
1N5334	3.6	3.42	3.78	350.0	2.5	500	1.00	150	1.0	1317.0
1N5335	3.9	3.71	4.10	320.0	2.0	500	1.00	50	1.0	1216.0
1N5336	4.3	4.09	4.52	290.0	2.0	500	1.00	10	1.0	1103.0
1N5337	4.7	4.47	4.94	260.0	2.0	450	1.00	5	1.0	1009.0
1N5338	5.1	4.85	5.36	240.0	1.5	400	1.00	1.0	1.0	930.0
1N5339	5.6	5.32	5.88	220.0	1.0	400	1.00	1.0	2.0	846.0
1N5340	6.0	5.70	6.30	200.0	1.0	300	1.00	1.0	3.0	790.0
1N5341	6.2	5.89	6.51	200.0	1.0	200	1.00	1.0	3.0	765.0
1N5342	6.8	6.46	7.14	175.0	1.0	200	1.00	10.0	5.2	700.0
1N5343	7.5	7.13	7.88	175.0	1.5	200	1.00	10.0	5.7	630.0
1N5344	8.2	7.79	8.61	150.0	1.5	200	1.00	10.0	6.2	580.0
1N5345	8.7	8.27	9.14	150.0	2.0	200	1.00	10.0	6.6	545.0
1N5346	9.1	8.65	9.56	150.0	2.0	150	1.00	7.5	6.9	520.0
1N5347	10.0	9.50	10.50	125.0	2.0	125	1.00	5	7.6	475.0
1N5348	11.0	10.45	11.55	125.0	2.5	125	1.00	5	8.4	430.0
1N5349	12.0	11.40	12.60	100.0	2.5	125	1.00	2	9.1	395.0
1N5350	13.0	12.35	13.65	100.0	2.5	100	1.00	1	9.9	365.0
1N5351	14.0	13.30	14.70	100.0	2.5	75	1.00	1	10.6	340.0
1N5352	15.0	14.25	15.75	75.0	2.5	75	1.00	1	11.5	315.0
1N5353	16.0	15.20	16.80	75.0	2.5	75	1.00	1	12.2	295.0
1N5354	17.0	16.15	17.85	70.0	2.5	75	1.00	0.5	12.9	280.0
1N5355	18.0	17.10	18.90	65.0	2.5	75	1.00	0.5	13.7	265.0
1N5356	19.0	18.05	19.95	65.0	3.0	75	1.00	0.5	14.4	250.0
1N5357	20.0	19.00	21.00	65.0	3.0	75	1.00	0.5	15.2	237.0
1N5358	22.0	20.90	23.10	50.0	3.5	75	1.00	0.5	16.7	216.0
1N5359	24.0	22.80	25.20	50.0	3.5	100	1.00	0.5	18.2	198.0
1N5360	25.0	23.75	26.25	50.0	4.0	110	1.00	0.5	19.0	190.0
1N5361	27.0	25.65	28.35	50.0	5.0	120	1.00	0.5	20.6	176.0
1N5362	28.0	26.60	29.40	50.0	6.0	130	1.00	0.5	21.2	170.0
1N5363	30.0	28.50	31.50	40.0	8.0	140	1.00	0.5	22.8	158.0
1N5364	33.0	31.35	34.65	40.0	10.0	150	1.00	0.5	25.1	144.0
1N5365	36.0	34.20	37.80	30.0	11.0	160	1.00	0.5	27.4	132.0
1N5366	39.0	37.05	40.95	30.0	14.0	170	1.00	0.5	29.7	122.0
1N5367	43.0	40.85	45.15	30.0	20.0	190	1.00	0.5	32.7	110.0
1N5368	47.0	44.65	49.35	25.0	25.0	210	1.00	0.5	35.8	100.0
1N5369	51.0	48.45	53.55	25.0	27.0	230	1.00	0.5	38.8	93.0
1N5370	56.0	53.20	58.80	20.0	35.0	280	1.00	0.5	42.6	86.0
1N5371	60.0	57.00	63.00	20.0	40.0	350	1.00	0.5	42.5	79.0
1N5372	62.0	58.90	65.10	20.0	42.0	400	1.00	0.5	47.1	76.0
1N5373	68.0	64.60	71.40	20.0	44.0	500	1.00	0.5	51.7	70.0
1N5374	75.0	71.25	78.75	20.0	45.0	620	1.00	0.5	56.0	63.0
1N5375	82.0	77.90	86.10	15.0	65.0	720	1.00	0.5	62.2	58.0
1N5376	87.0	82.65	91.35	15.0	75.0	760	1.00	0.5	66.0	54.5
1N5377	91.0	86.45	95.55	15.0	75.0	760	1.00	0.5	69.2	52.5
1N5378	100.0	95.00	105.00	12.0	90.0	800	1.00	0.5	76.0	47.5
1N5379	110.0	104.50	115.50	12.0	125.0	1000	1.00	0.5	83.6	43.0
1N5380	120.0	114.00	126.00	10.0	170.0	1150	1.00	0.5	91.2	39.5
1N5381	130.0	123.50	136.50	10.0	190.0	1250	1.00	0.5	98.8	36.6
1N5382	140.0	133.00	147.00	8.0	230.0	1500	1.00	0.5	106.0	34.0
1N5383	150.0	142.50	157.50	8.0	330.0	1500	1.00	0.5	114.0	31.6
1N5384	160.0	152.00	168.00	8.0	350.0	1650	1.00	0.5	122.0	29.4
1N5385	170.0	161.50	178.50	8.0	380.0	1750	1.00	0.5	129.0	28.0
1N5386	180.0	171.00	189.00	5.0	430.0	1750	1.00	0.5	137.0	26.4
1N5387	190.0	180.50	199.50	5.0	450.0	1850	1.00	0.5	144.0	25.0
1N5388	200.0	190.00	210.00	5.0	480.0	1850	1.00	0.5	152.0	23.6

NOTICE

The information presented in this document is for reference only. Involving product optimization and productivity improvement, ChipNobo reserves the right to adjust product indicators and upgrade some technical parameters. ChipNobo is entitled to be exempted from liability for any delay or non-delivery of the information disclosure process that occurs.

本文件中提供的信息仅供参考。涉及产品优化和生产效率改善，ChipNobo 有权调整产品指标和部分技术参数的升级，所出现信息披露过程存在延后或者不能送达的情形，ChipNobo 有获免责权。

The product listed herein is designed to be used with residential and commercial equipment, and do not support sensitive items and specialized equipment in areas where sanctions do exist. ChipNobo Co., Ltd or anyone on its behalf, assumes no responsibility or liability for any damages resulting from improper use.

此处列出的产品旨在民用和商业设备上使用，不支持确有制裁地区的敏感项目和特殊设备，ChipNobo 有限公司或其代表，对因不当使用而造成的任何损害不承担任何责任。

For additional information, please visit our website <http://www.chipnobo.com>, or consult your nearest Chipnobo sales office for further assistance.

欲了解更多信息，请访问我们的网站 <http://www.chipnobo.com>，或咨询离您最近的 Chipnobo 销售办事处以获得进一步帮助。