


Applications

- Power amplifier
- Power switching

Features

- Low saturation voltage: $V_{CE(sat)} = -0.5V$ (Max.) ($I_C = -1A$)
- High current output up to 2A

TO-126B



Absolute Maximum Ratings (Ta=25°C)

Parameter		Symbol	Value	Unit
Collector-base voltage		BV_{CBO}	-50	V
Collector-emitter voltage		BV_{CEO}	-50	V
Emitter-base voltage		BV_{EBO}	-5	V
Collector current		I_C	-2	A
Collector power dissipation	Ta=25°C	P_C	1.5	W
	Tc=25°C		10	
Junction temperature		T_j	150	°C
Storage temperature		T_{stg}	-55~150	°C

Electrical Characteristics (Ta=25°C)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	BV_{CBO}	$I_C = -100\mu A, I_E = 0$	-50			V
Collector-emitter breakdown voltage	BV_{CEO}	$I_C = -1mA, I_B = 0$	-50			V
Emitter-base breakdown voltage	BV_{EBO}	$I_E = -100\mu A, I_C = 0$	-5			V
Collector cut-off current	I_{CBO}	$V_{CB} = -50V, I_E = 0$			-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = -5V, I_C = 0$			-0.1	μA
DC current gain*	$h_{FE(1)}$	$V_{CE} = -2V, I_C = -0.5A$	70		400	
	$h_{FE(2)}$	$V_{CE} = -2V, I_C = -1.5A$	40			
Collector-emitter saturation voltage*	$V_{CE(sat)}$	$I_C = -1A, I_B = -0.05A$			-0.5	V
Base -emitter saturation voltage*	$V_{BE(sat)}$	$I_C = -1A, I_B = -0.05A$			-1.2	V
Transition frequency	f_T	$V_{CE} = -2V, I_B = -0.5A$		100		MHz
Output capacitance	C_{ob}	$V_{CB} = -10V, I_E = 0, f = 1MHz$		30		pF

* Pulse Test: PW=300 μ s, duty Cycle=1.5% Pulsed

$h_{FE(1)}$ Classification

Classification	O	Y	G
Range	70~140	120~240	200~400

Typical Characteristics




Figure 1. Static Characteristic




Figure 2. DC current Gain




Figure 3. Collector-Emitter Saturation Voltage




Figure 4. Base-Emitter Saturation Voltage




Figure 5. Safe Operating Area




Figure 6. Power Derating

Package Dimensions

Dim	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	2.40	2.80	0.094	0.110
A1	1.00	1.40	0.039	0.055
b	0.66	0.86	0.026	0.034
b1	1.17	1.37	0.046	0.054
c	0.40	0.60	0.016	0.024
D	7.30	7.70	0.287	0.303
E	10.60	11.00	0.417	0.433
e	2.25	2.33	0.089	0.092
e1	4.50	4.66	0.177	0.183
L	14.00	15.00	0.551	0.591
L1	1.90	2.50	0.075	0.098
Φ	3.10	3.30	0.122	0.130

NOTICE

The information presented in this document is for reference only. Involving product optimization and productivity improvement, ChipNobo reserves the right to adjust product indicators and upgrade some technical parameters. ChipNobo is entitled to be exempted from liability for any delay or non-delivery of the information disclosure process that occurs.

本文件中提供的信息仅供参考。涉及产品优化和生产效率改善，ChipNobo 有权调整产品指标和部分技术参数的升级，所出现信息披露过程存在延后或者不能送达的情形，ChipNobo 有获免责权。

The product listed herein is designed to be used with residential and commercial equipment, and do not support sensitive items and specialized equipment in areas where sanctions do exist. ChipNobo Co., Ltd or anyone on its behalf, assumes no responsibility or liability for any damages resulting from improper use.

此处列出的产品旨在民用和商业设备上使用，不支持确有制裁地区的敏感项目和特殊设备，ChipNobo 有限公司或其代表，对因不当使用而造成的任何损害不承担任何责任。

For additional information, please visit our website <http://www.chipnobo.com>, or consult your nearest Chipnobo sales office for further assistance.

欲了解更多信息，请访问我们的网站 <http://www.chipnobo.com>，或咨询离您最近的 Chipnobo 销售办事处以获得进一步帮助。